



产品型号 Models

产品型号 Models		输入电压(Vdc) Input voltage range	输出电压 (Vdc) Output voltage	输出电流(A) Output current	纹波 (mv) Ripple and noise	效率 (%) Efficiency
单 路	MDN800-12S12	12V(9~18V)	12V	67A	120	84
	MDN800-12S24		24V	33.3A	200	84
	MDN800-12S48		48V	16.7A	400	85
	MDN800-24S12	24V(18~36V)	12	62.5	120	84
	MDN1000-24S24		24	41.7	200	85
	MDN1200-24S28		28	42.8	280	87
	MDN1500-24S48		48	31.3	400	89
	MDN2400-36S48	36V(24~48V)	48	50	400	90
	MDN1500-36S55		55	27.3	550	88
	MDN1000-48S12	48V(36~72V)	12	83.3	120	87
	MDN2000-48S24		24	83.3	200	89
	MDN2000-48S48		48	41.7	400	90
	MDN3000-50S48	50V(30~75V)	48	62.5	400	90
	MDN800-110S12	110V(70~140V)	12	66.7	120	86
	MDN1500-110S24		24	62.5	200	88
	MDN2000-110S28		28	71.4	280	89
	MDN1500-110S48		48	31.3	400	89
	MDN2000-110S48		48	41.7	400	90
	MDN1200-300S12	300V(200~400V)	12	100	120	88
	MDN1500-300S15		15	100	150	88
	MDN1500-300S24		24	62.5	200	90
MDN2600-300S48	48		54	400	90	
MDN1200-600S12	600V(400~800V)	12	100	120	87	
MDN2000-600S24		24	83.3	200	90	
MDN2000-600S48		48	41.7	400	90	
双 路	MDN800-12D12&12	12V(9~18V)	12/12	33.3/33.3	120/120	84
	MDN800-12D12&24		12/24	33.3/16.7	120/200	84

MDN1000-24D12&24	24V(18~36V)	12/24	41.7/20.8	120/200	86
MDN1500-24D24&48		24/48	20.8/20.8	200/400	88
MDN2000-48D24&48	48V(36~72V)	24/48	41.7/20.8	200/400	90
MDN800-110D12&12	110V(70~140V)	12/12	33.3/33.3	120/120	86
MDN1500-110D12&24	110V(60~160V)	12/24	41.7/41.7	120/200	88
MDN2000-110D24&24	110V(80~180V)	24/24	41.7/41.7	200/200	89
MDN1500-300D12&24	300V(200~400V)	12/24	41.7/41.7	120/200	88
MDN2000-300D24&24		24/24	41.7/41.7	200/200	90
MDN1500-600D12&24	600V(400~800V)	12/24	41.7/41.7	120/200	88
MDN2000-600D24&24		24/24	41.7/41.7	200/200	90

外形尺寸与引脚定义 (Mechanical drawing and pin definition) 尺寸: 400×310×94mm

