



产品型号 Models		输入电压(Vdc) Input voltage range	输出电压 (Vdc) Output voltage	输出电流(A) Output current	纹波 (mv) Ripple and noise	效率 (%) Efficiency	
单路	MDT500-12S12	12V(9~18V)	12V	41.7A	120	84	
	MDT500-12S24		24V	20.8A	200	84	
	MDT500-12S48		48V	10.4A	400	85	
	MDT600-24S12	24V(18~36V)	12	50	120	84	
	MDT800-24S24		24	33.3	200	85	
	MDT1000-24S28		28	35.7	280	87	
	MDT1200-24S48		48	25	400	89	
	MDT600-48S12	48V(36~72V)	12	50	120	87	
	MDT1000-48S24		24	41.7	200	89	
	MDT1200-48S48		48	25	400	90	
	MDT800-110S12	110V(70~140V)	12	66.7	120	86	
	MDT1000-110S24		24	41.7	200	88	
	MDT800-110S48		48	16.7	400	89	
	MDT1000-110S48		48	20.8	400	89	
	MDT1200-110S48		48	25	400	90	
	MDT750-300S12	300V(200~400V)	12	62.5	120	86	
	MDT750-300S15		15	50	150	88	
	MDT1000-300S24		24	41.7	200	90	
	MDT1000-300S48		48	20.8	400	86	
	MDT750-600S12	600V(400~800V)	12	62.5	120	87	
	MDT1000-600S24		24	41.7	200	90	
	MDT1200-600S48		48	25	400	90	
	双路	MDT500-12D12&12	12V(9~18V)	12/12	20.8/20.8	120/120	84
		MDT500-12D12&24		12/24	20.8/10.4	120/200	84
MDT800-24D12&24		24V(18~36V)	12/24	33.3/16.7	120/200	86	
MDT1000-24D24&24			24/24	25/25	200/200	88	
MDT800-48D12&24		48V(36~72V)	12/24	33.3/16.7	200/400	90	
MDT1200-48D24&48			24/48	25/12.5	200/400	90	

MDT810-74D24&14	74V(50~90V)	24/14	25/15	200/140	88
MDT1410-74D24&14	74V(50~100V)	24/14	50/15	200/140	90
MDT1000-110D24&24	110V(70~140V)	24/24	20.8/20.8	200/200	89
MDT800-300D12&24	300V(200~400V)	12/24	33.3/16.7	120/200	88
MDT1200-300D24&24		24/24	25/25	200/200	90
MDT800-600D12&24	600V(400~800V)	12/24	33.3/16.7	120/200	88
MDT1200-600D24&24		24/24	25/25	200/200	90

外形尺寸与引脚定义 (Mechanical drawing and pin definition) 尺寸: 333×241×94mm

