

## CSF100-S SPECIFICATIONS

	MODEL	CSF100-3R3	CSF100-05	CSF100-09	CSF100-12	CSF100-15	CSF100-24	CSF100-48
INPUT	VOLTAGE, FREQUENCY	AC85V-132V / 170V-264V or DC240V~370V (Auto selector), 50/60Hz (47~440Hz or DC)						
	CURRENT	110V~1.2A 220V~0.9A	110V~2.0A, 220V~1.2A					
	EFFICIENCY (AC220V)	75% typ	82% typ	82% typ	85% typ	85% typ	85% typ	85% typ
	INRUSH CURRENT	20A typ(ACIN 110V, I <sub>o</sub> =100%), 40A typ(ACIN 220V, I <sub>o</sub> =100%) at cold start.						
OUTPUT	VOLTAGE [V]	3.3	5	9	12	15	24	48
	CURRENT [A]	20	20	11	8.4	6.7	4.2	2.1
	REGULATION, LINE [mV]	25 Max	25 Max	45 Max	60 Max	75 Max	120 Max	240 Max
	REGULATION, LOAD [mV]	50 Max	50 Max	90 Max	120 Max	150 Max	240 Max	480 Max
	RIPPLE [mVp-p]	80 Max	80 Max	120 Max	120 Max	120 Max	120 Max	150 Max
	RIPPLE, NOISE [mVp-p]	120 Max	120 Max	150 Max	150 Max	150 Max	150 Max	250 Max
	TEMPERATURE DRIFT 0~+50°C [mV]	50 Max	75 Max	135 Max	180 Max	225 Max	360 Max	720 Max
	RISE TIME [ms]	600 Max (ACIN 100V, I <sub>o</sub> =100%)						
	HOLDING TIME [ms]	17 typ (ACIN 100V, I <sub>o</sub> =100%)						
PROTECTION CIRCUIT	OVER CURRENT PROTECTION	Works at over 105% of rating and recovers automatically						
	OVER VOLTAGE PROTECTION	Works at 115~140% of rating						
ELECTRICALLY ISOLATED	INPUT-OUTPUT	AC3,000V 1 minute current 20mA, DC 500V 100MΩ (At room temperature & Humidity)						
	INPUT-CASE, FG	AC2,000V 1 minute current 20mA, DC 500V 100MΩ (At room temperature & Humidity)						
	OUTPUT-CASE, FG	AC500V 1 minute current 100mA, DC 500V 100MΩ (At room temperature & Humidity)						
ENVIRONMENT	OPERATING TEMP AND HUMID	-10~+70°C(Required Derating), 20~90% RH(Non Condensing)						
	STORAGE TEMP AND HUMID	-20~+75°C, 20~90% RH(Non Condensing)						
	VIBRATION	10~55Hz at 1G, 3 minutes period, 30 minutes along X, Y and Z axis						
	IMPACT	10G for 20ms, once on each X, Y and Z axis						
SAFETY	SAFETY REGULATION	UL, C-UL, CE, CB						
	LINE CONDUCTED RF VOLTAGE	Complied with FCC Part 15, VCCI-A, CISPR22-A, EN55022-A						

## CSF100-S EXTERNAL VIEW

