

CSF75-S SPECIFICATIONS

	MODEL	CSF75-3R3	CSF75-05	CSF75-09	CSF75-12	CSF75-15	CSF75-24	CSF75-48*
INPUT	VOLTAGE, FREQUENCY	AC100-240V (AC85~264V or DC120~370V), 50/60Hz (47~440Hz or DC)						
	CURRENT	110V~1.0A 220V~0.6A	110V~1.3A, 220V~0.8A					
	EFFICIENCY (AC220V)	75% typ	78% typ	81% typ	82% typ	81% typ	82% typ	82% typ
	INRUSH CURRENT	20A typ(ACIN 110V, I _o =100%), 40A typ(ACIN 220V, I _o =100%) at cold start.						
OUTPUT	VOLTAGE [V]	3.3	5	9	12	15	24	48
	CURRENT [A]	15	15	8.4	6.4	5	3.2	1.6
	REGULATION, LINE [mV]	25 Max	25 Max	45 Max	60 Max	75 Max	120 Max	240 Max
	REGULATION, LOAD [mV]	50 Max	50 Max	90 Max	120 Max	150 Max	240 Max	480 Max
	RIPPLE [mVp-p]	80 Max	80 Max	120 Max	120 Max	120 Max	120 Max	150 Max
	RIPPLE, NOISE [mVp-p]	120 Max	120 Max	150 Max	150 Max	150 Max	150 Max	250 Max
	TEMPERATURE DRIFT 0~+50°C [mV]	50 Max	75 Max	135 Max	180 Max	225 Max	360 Max	720 Max
	RISE TIME [ms]	200 Max (ACIN 100V, I _o =100%)						
PROTECTION CIRCUIT	HOLDING TIME [ms]	17 typ (ACIN 100V, I _o =100%)						
	OVER CURRENT PROTECTION	Works at over 105% of rating and recovers automatically						
ELECTRICALLY ISOLATED	OVER VOLTAGE PROTECTION	Works at 115~140% of rating						
	INPUT-OUTPUT	AC3,000V 1 minute current 20mA, DC 500V 100MΩ (At room temperature & Humidity)						
	INPUT-CASE, FG	AC2,000V 1 minute current 20mA, DC 500V 100MΩ (At room temperature & Humidity)						
ENVIRONMENT	OUTPUT-CASE, FG	AC500V 1 minute current 100mA, DC 500V 100MΩ (At room temperature & Humidity)						
	OPERATING TEMP AND HUMID	-10~+70°C(Required Derating), 20~90% RH(Non Condensing)						
	STORAGE TEMPAND HUMID	-20~+75°C, 20~90% RH(Non Condensing)						
	VIBRATION	10~55Hz at 1G, 3 minutes period, 30 minutes along X, Y and Z axis						
SAFETY	IMPACT	10G for 20ms, once on each X, Y and Z axis						
	SAFETY REGULATION	UL, C-UL, CE, CB (NOTICE: CSF75-48 Model Exclusion)						-
	LINE CONDUCTED RF VOLTAGE	Complied with FCC Part 15, VCCI-A, CISPR22-A, EN55022-A						

CSF75-S EXTERNAL VIEW

